

# BLOCKOUT TEXTILE-PRINTABLE BOTH SIDES



## Technical Data Sheet

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
<b>STD WIDTH</b>	/	0.914m/ 1.27m/ 1.37m/1.52m	36"/50"/54"/60"
<b>STD LENGTH</b>	/	18m / 30m	19.69yd / 32.7yd
<b>WEIGHT</b>	/	240g/sq.m	7oz/sq.yd
<b>BASE FABRIC</b>	DIN 60001	POLYESTER	POLYESTER
<b>YARN Dtex</b>	DIN EN ISO 2060	165Dtex	150denier
<b>TENSILE STRENGTH</b>	DIN EN ISO 1421	195x110N/5cm	43x24lbs/inch
<b>TEAR STRENGTH</b>	DIN 53363	19x21N	4.5x5.2lbs

### INK PRINTABILITY

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINT	WATERBASE
*****	*****	*****	*****	*****	*****

DYE TRANSFER	DYE DIRECT



<b>Application/ Features</b>	Double Sided Solvent printable, No Fraying, Dimension Stable, Good Flatness, Environmentally Friendly (no PVC), Excellent alternative to PVC banners, Best Suited for Roll-Up Display Systems.
<b>Note:</b>	All above information shall only be used as a guide: buyers shall independently test and determine the products suitability. the mentioned data are an average of test results and should not be used for the purpose of lawsuit or warranty.