

18oz BLOCKOUT



Technical Data Sheet

ARTICLE No.	TEST METHOD	METRIC	IMPERIAL
TOTAL WEIGHT	DIN EN ISO 2286-2	610g/m ²	18oz/sq.yd.
BASE FABRIC	DIN 60001	POLYESTER	POLYESTER
YARN	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
TENSILE STRENGTH	DIN EN ISO 1421	1550 x 1210 N/5cm	173 x 136 lbs/inch
TEAR STRENGTH	DIN 53363	196 x 298 N	44 x 67 lbs
ADHESION	DIN 53357	NO DELAMINATION	
FLAME RESISTANCE	DIN 4102	NFPA 701, B1, M2	
WIDTH	N/A	MAX 320cm	126 INCH

INK PRINTABILITY

SOLVENT	ECO-SOLVENT	UV	SCREEN PRINTING	LATEX	DYE TRANSFER	DYE DIRECT
*****	*****	*****	*****	*****		



Application/ Features	* Suitable for demanding outdoor conditions where opacity or double sided printing is required.
Note:	All above information shall only be used as a guide: buyers shall independently test and determine the products suitability. the mentioned data are an average of test results and should not be used for the purpose of lawsuit or warranty.